

**THE SHAW GROUPLIMITED
MATERAIL SAFETY DATA SHEET**



MATERIAL – Clay Brick

SECTION I – PRODUCT IDENTIFICATION

Product Name: Clay Brick
Product Use: Construction/Building Material

Supplier name and address:
The Shaw Group Limited
P.O. Box 2130
Lantz, Nova Scotia
B2S 3G4

Manufacturer name and address:
Same as manufacturer

Emergency Tel. #: (902) 883-2201 (daytime only)
Fax #: (902) 883-1273
Chemical Name: Mixture

Emergency Tel. #: Same
Fax #: Same
Molecular weight: N. Ap.

SECTION II - INGREDIENTS

Ingredients:	CAS #	%	ACGIH TLV	OSHA PEL
Aluminum Silicates Dust	Various	70 – 85	1 mg/m ³	15 mg/m ³ as Al, 5mg/m ³ Resp.
Iron Compounds	Various	0 - 10	5 mg/m ³	N.Ap.
Calcium Oxide	1305-78-8	0 - 2	2 mg/m ³	5mg/m ³
Calcium Compounds	Various	0 – 2	10 mg/m ³	N.Ap.
Crystalline Silica	14808-60-7	7 – 15	.025 mg/m ³	16 mppcf
Amorphous Silica	61790-53-2	40 – 45	10 mg/m ³	10 mg/m ³
Barium Compounds	Various	0 – 2	.5 mg/m ³ as Ba	.5 mg/m ³ as Mn(C)
Magnesium Compounds	Varoius	0 – 2	10 mg/m ³	N.Ap.
Potassium Oxide	Varoius	0 – 4	N.Av.	N.Av

SECTION III – PHYSICAL DATA

Physical State:	Inert Solid	Freezing Point:	N. Ap.
Odour and appearance:	No Odor. Textured Rectangular Solid	pH:	N. Ap.
Odour threshold:	N. Ap.	Vapour density (air 1):	N. Ap.
Specific gravity:	N. Ap.	Evaporation rate (BuAc 1):	N. Ap.
Coefficient if water/oil distribution:	N. Ap.	Volatility, %:	N. Ap.
Vapour pressure (mmHg):	N. Ap.	Solubility in water:	N. Ap.
Boiling point:	N. Ap.	Density g/ml:	N. Ap.

SECTION IV – FIRE AND EXPLOSION DATA

Conditions of flammability:	N. Ap.
Means of extinction:	N. Ap.
Sensitivity to mechanical impact/static discharge:	N. Ap.
Flash point (Method):	N. Ap.
Upper/Lower flammable limits (% by volume):	N. Ap.
Auto-ignition temperature:	N. Ap.
Hazardous combustion products:	N. Ap.

SECTION V – REACTIVITY DATA

Stability:
Incompatible materials: N. Ap.
Conditions of reactivity: N. Ap.
Hazardous decomposition products: N. Ap.

N. Av. Not Available
N. Ap. Not Applicable

MATERIAL – Clay Brick

SECTION VI – TOXICOLOGICAL PROPERTIES

LD₅₀ of material:	N. Ap.
LC₅₀ of material:	N. Ap.
Exposure limit:	N.Ap
Route of entry:	Inhalation hazard only when dry sawing.
Effects of Chronic Exposure or Product:	Effects of chronic exposure are only associated with repeated, frequent, excessive exposure to dusts during dry sawing. Crystalline silica is a known cause of silicosis a progressive chronic lung disease and is a group 1 carcinogen.
Irritancy of Product:	
Ingestion:	N. Ap.
Acute effects:	N. Ap.
Other effects:	N. Ap.
Sensitization to product:	N. Ap.
Synergistic product:	N. Ap.
Other effects:	N. Ap.

SECTION VII – PREVENTIVE MEASURES

Personal Protective Equipment:	
Gloves (Specify):	Gloves or hand leathers to protect skin from abrasion during handling.
Respiratory (Specify):	Respiratory protection is required if cutting, crushing, or grinding of product is present. A properly fitted and approved NIOSH respirator as per standard Z94.4 is needed if silica dust exceeds the TLV.
Eye (Specify):	Approved safety glasses with side shields to protect eye from brick chips during sawing or handling. Full face shield may provide additional protection.
Footwear (Specify):	Approved steel toed safety footwear is recommended to be worn.
Clothing (Specify):	N. Ap.
Other (Specify):	N. Ap.
Engineering Controls (e.g. ventilation, enclosed process, specify):	A wet saw method is recommended to minimize dust production during sawing.
Leak and Spill Procedure:	N. Ap.
Waste Disposal:	Non-hazardous Waste
Handling Procedures and Equipment:	Avoid dry sawing. Wear approved respirator if dust produced during sawing.
Storage Requirements:	N. Ap.
Special Shipping Information:	This product is not regulated under TDG

SECTION VIII – FIRST AID MEASURES

Skin:	General first aid treatment for minor skin abrasions during handling.
Eye:	Seek appropriate health care if eye surface scratched. Do not attempt to remove embedded objects in eye.
Inhalation:	Remove to fresh air if dust, during sawing causes difficulty breathing. Seek appropriate health care.
Ingestion:	N. Ap.

SECTION IX – PREPARATION DATE OF M.S.D.S.

Prepared by: Brady Hawley, Division Engineer	Phone: 1-902-883-2201	Date: May 29, 1995
		Rev.: May 1997
		Rev.: May 2000
		Rev.: February 2003
		Rev.: October 2005
		Rev.: October 2007
		Rev.: September 2010
		Rev.: Mar 2012
		Rev.: May 2015

This information and recommendations contained herein are offered as a service to our customers/employees and are not intended to relieve the user from its responsibility to investigate and understand other pertinent sources of information and to comply with laws and procedures applicable to safer handling and use of materials. This information is believed to be accurate at the time of preparation and obtained from sources generally believed to be reliable. However, The Shaw Group Limited makes no warranty concerning their accuracy and will not be liable for claims relating to any party's use of or reliance on information contained herein.