



SMITH **STONE**


We are pleased to introduce our new residential line, Smith Stone, launching in two, contemporary colours, Polar and Oxenden. Corners are on every unit in both sizes.

Smith Stone projects the perfect balance of a moderately rugged stone face with the contemporary appeal of clean, horizontal lines randomly, yet tastefully, broken with variable length and height dimensions. Together, these qualities make Smith Stone a perfect reflection of our times and your sophisticated good taste.

COLOUR



Polar *Quick Ship*



Oxenden



SPECIFICATIONS

- Smith Stone is a quality Concrete Masonry Unit.
- Smith Stone exceeds the CSA A165.2 Series-04 and the ASTM C-55-11 specifications.
- Smith Stone will not flake or deteriorate whether it is used above grade, at grade or even below grade.
- Maximum water absorption by mass not to exceed 8 percent.
- Recommended to be installed with Type 'N' masonry cement (see TEK 9-1A Mortars for Concrete Masonry).
- Smith Stone is manufactured using an integral water repellent agent which inhibits water absorption and efflorescence for a lifetime of performance.
- Minimum compressive strength 4,000 PSI.
- Recommended mortar joint 3/8".
- Cold weather construction – refer to installation guidelines.

Size	Width	Height	Length	Pcs./sq ft	Wt/Pc.
2" Cube	3.5"	2.25"	8"/12"/16"/24"	Varies	Varies
4" Cube	3.5"	4.875"	8"/12"/16"/24"	Varies	Varies

Size	Wt Per Cube	Pallet Size	Coverage Per Cube
2" Cube	2760 lb / 1255 kg	47" Wide x 40" Deep	94 sq ft / 8.73 sq m
4" Cube	2990 lb / 1360 kg	47" Wide x 40" Deep	94 sq ft / 8.73 sq m